

156 Heugh Rd, Walmer, Port Elizabeth www.allcut.co.za 041 581 3627

Goscor Power Products

11 553

ISO9001 (E 🤓 SASO SONCAP EUI 🖗 EPA





Trusted Equipment Solutions

Diese

Generator Range Powered by heavy Noise level 5ldb (A) at

20KVA Super Silenced Industrial engines **Diesel Generator**

(7m)

1500 R.P.M (4 cylinder; water cooled)

DIESEL GENERA	TORS											
Model	Frequency Hz	Max. Output kW	Rated Output kW	DC Output V-A	Rated Voltage V	Phase	Displacement	Starting System	Fuel Tank Capacity	Oil Capacity	Packing Dim. (LxWxH) mm	Gross Weight (kg)
5GF-LDEDB	50	4.8	4.4	12V/8.3A	240	Single	406/418cc	Electric	161	1.651	945x550x770	165
5GF-LDEDB_ATS	50	4.5	4.4	12V/8.3A	240	Single	406/418cc	Electric/ATS	161	1.651	945x550x770	165
5GF-MEF4	50	4.8	4.4	12V/8.3A	240	Single	406/418cc	Rope	151	1.651	760x500x650	120
LT-20SS3	50	20.6	18.75	14V/20A	230/400	3 Phase	2190cc	Electric/ATS	381	6.91	1550x720x810	750

553

Lutiar

Alert

As the generator is operating, the system will alert and close the generator if the parameter exceeds the max. One which is set by the user. For various overload protection alert needs as:

> Low voltage protection High voltage protection Low voltage protection of the battery High voltage protection of the battery Engine temperature protection

> > Low oil protection

The protection of starting unsuccessfully (it can't be cancelled)

The protection of stopping unsuccessfully (it can't be cancelled)

*You can stop alerting and come into the main screen by pressing the menu key after alert

Diesel Generator 5000w (with oil sensor)

POWER

PRODUCTS



Diesel 5000W Silent with Automatic **Mains Failure Panel**

===


Petrol Generator Range

Powered by heavy duty Lutian Industrial engines



GASOLINE	GASOLINE GENERATORS											
Model	HP	Starting System	Displacement	Generator Output		Fuel Tank	Continuous	Min. Fuel	Noise		Packing Dim.	Gross Weight
			biplacement	Rated	Max	Capacity	Operating Time	Consumption	Level	on capacity	(LXVVXH) mm	(kg)
LT-2500S	5.5	Recoil	163cc	2	2.2	151	13h	360g/kW . H	65dB	0.61	605x455x460	40
LT-2500ES	5.5	Electric	163cc	2	2.2	151	13h	360g/kW . H	65dB	0.61	605x455x460	40
LT-6500ES	15	Electric	420cc	6	6.5	251	8h	313g/kW . H	78dB	1.11	695x525x545	85
3500LBI	6	Recoil	150cc	3	3.3	5.71	3.1h	230g/kW . H	63dB	0.91	595x355x510	31.5





.....

GASOLINE WI	ELDER/GENI	ERATOR							
Model	Welder			ļ	AC Generator		Packing Dim.	Gross	Electrode
	Output	Current	Voltage	Output	Fequency	Voltage	(LxWxH) mm	Weight (kg)	Size (mm)
LTW-190B	3.64kW	200A	25V	5kW	50	230V	810x520x535	85	2.2-5mm

Lutian

GENERATOR



DIESEL WELDER/GENERATOR										
Model	Welder			AC Generator			Packing Dim.	Gross	Electrode	
	Output	Current	Voltage	Output	Fequency	Voltage	(LxWxH) mm	Weight (kg)	Size (mm)	
5GF-MEW	3.64kW	190A	26V	2kW	50	230V	760x500x650	108	2.2-5mm]



POWER PRODUCTS



www.allcut.co.za 041 581 3627

Generator & Welder Combo's

Powered by heavy duty Lutian Industrial engines

COMES STANDARD WITH AVR AND 100% COPPER WINDINGS!

CONSTANT INNOVATION Throughout Time





ENGINES	NGINES											
Model	Туре	Fuel	Maximum Output (HP)	Starting System	Fuel Tank Capacity (L)	Packing Dim. (LxWxH) mm	Gross Weight (kg)					
LT-168FA	2:1 Reduction	Petrol	5.5	Recoil	3.6	390x360x350	16					



POWER PRODUCTS Diesel 2:1 Reduction (Concrete Mixer Engine)

ENGINES							
Model	Туре	Fuel	Maximum Output (HP)	Starting System	Fuel Tank Capacity (L)	Packing Dim. (LxWxH) mm	Gross Weight (kg)
LT-178FA	2:1 Reduction	Diesel	7	Recoil	3.5	460x440x500	33





www.allcut.co.za 041 581 3627

Lutian Engines Petrol & Diesel

Powered by heavy duty Lutian Industrial engines

DESIGNED FOR Exceptional Performance



PLUNGER PL	JMPS - E	ARE ON	LY		0			X		
Model	Bore (mm)	Stroke (mm)	Max. Pressure bar	Max. Pressure PSI	Flow L/min	Flow GPM	RPM	Power Required HP	Packing Dim. (LxWxH) cm	Gross Weight (kg)
3WZ-1507A	15	7	186	2700	12.6	3.32	3400	6.5	36x28x25	8.5
3WZ-1508A	15	8	220	3200	14.4	3.8	3400	9	36x28x25	8.5
3WZ-1510A	15	10	248	3600	18	4.76	3400	13	36x28x25	8.9
3WZ-1808B	18	8	180	2600	17.1	4.51	2800	5.5kW	38x30x26	11

il.

Electric 380v High Pressure Cleaner

Bare Pump

HIGH PRESSU	RE WASHER	RS - ELECTI	RIC HP PUMP	S					
Model	Electric Motor (kW)	Voltage (V)	Revolution (rpm)	Max. Pressure bar	Max. Pressure PSI	Flow L/min	Flow GPM	Packing Dim. (LxWxH) cm	Gross Weight (kg)
18M36-7.5T4	7.5	380	1450	248	3600	16	4.24	88X63X63	89
20M39-5.5T4	5.5	380	1450	270	3900	10.9	2.88	88X63X63	89









156 Heugh Rd, Walmer, Port Elizabeth www.allcut.co.za 041 581 3627

High Pressure Pump Range



Diesel High Pressure Cleaner

HIGH PRESS	HIGH PRESSURE WASHERS - DIESEL POWERED HP PUMPS										
Model	Horse Power (HP)	Revolution (rpm)	Max. Pressure bar	Max. Pressure PSI	Water Flow L/min	Water Flow GPM	Packing Dim. (LxWxH) cm	Gross Weight (kg)			
15D36-10C	10	3200	248	3600	18.0	4.76	77x51.5x68	99.5			
18D35-10C	10	3200	240	3500	20.7	5.47	77x51.5x68	99.5			
15D28-7C	7	3200	193	2800	14.4	3.8	77x51.5x68	74			

High Pressure Cleaner with Subaru Engine

	HIGH PRESS	URE WASH	IERS - PETRO	L POWER I	HP PUMPS					100
	Model	Horse Power (HP)	Revolution (rpm)	Max. Pressure bar	Max. Pressure PSI	Water Flow L/min	Water Flow GPM	Engine	Packing Dim. (LxWxH) cm	Gross Weight (kg)
	15G27/EX17	6	3400	186	2700	12,6	3,32	EX17	70x56x57.5	42
	15G32/EX27	9	3400	220	3200	14.4	3.8	EX27	81.5x48.5x62.5	56
P	15G36/EX40	14	3400	248	3600	18.0	4.76	EX40	81.5x51.5x65	60



Fertilizer	
Pumps	

High Head Pumps

FERTIZLIZER PUMPS									
Model	Engine	Inlet & Outlet Inside Dia.	Pump Lift (m)	Suction Height (m)	Max. Capacity (m³/h)	Packing Dim. (LxWxH) cm	Gross Weight (kg)		
ТВ50	EY20	50mm (2")	30	7	35	520x380x470	22		
LTEX17F20H	EX17	50mm (2")	65	7	35	520x380x450	26		

VATER PUMPS	5 PETROL					
Model	Inlet & Outlet Inside Dia.	Pump Lift	Suction Height	Max Capacity	Packing Dim. (LxWxH) mm	Gross Weight (kg)
LT-20XC168F	50mm (2")	23m	7m	30m³/hr	485x380x405	23
LT-30XC168F	80mm (3")	28m	7m	60m³/hr	520x380x450	25



POWER PRODUCTS



156 Heugh Rd, Walmer, Port Elizabeth www.allcut.co.za 041 581 3627



156 Heugh Rd, Walmer, Port Elizabeth Water Pump Range www.allcut.co.za 041 581 3627



Diesel Pumps (air-cooled engines)

WATER PUMPS DIESEL										
Model	Size	Max. Capacity (m³/h)	Pump Lift (m)	Suction Head (m)	Rated Output [kW(HP]	Displacement (cc)	Packing Dim. (LxWxH) mm	Gross Weight (kg)		
50-KB2	2"	22	25	7	2.5(3.4)	211	535x420x510	37		
80-KB3	3"	36	28	7	3.8(5.2)	296	560x455x560	45		
100-KB4	4"	64	25	7	6.5(9.0)	406	660x490x610	65		
LT-178F20H	2"	30	65	7	3.8(5.2)	296	560x455x560	48		
LT-186F30H	3"	40	70	7	6.5(9.0)	406	660x490x610	65		



Other Goscor Solutions:



Our products are serviced by our dealer network nationwide, so if you want to purchase a top of the range product and get top performance which is backed nationally give us a call at:



A proud member of the Goscor Group of Companies





Trusted Equipment Solutions

